



Herts Glass
& Security Solutions LTD

EXPERTS
IN GLAZING
& SECURITY
SOLUTIONS

Herts Glass & Security Solutions Ltd proudly excels in producing cost-effective, creative, and innovative glazing and security solutions. Our exceptional team wholeheartedly embraces the essence of delivering impeccable customer care coupled with top-notch craftsmanship.

Our services cater to both the commercial and domestic sectors, extending our expertise to homeowners, architects, builders, and consultants, enabling them to manifest their visionary concepts throughout the picturesque landscapes of Hertfordshire and its neighbouring areas.

Embracing an extensive array of glazing and security solutions, we offer a plethora of options such as the exquisite Bi-Folds, the finest UPVC products, the regal Aluminium Front Doors, the indispensable Fire Exit Doors, the heavenly Skylights & Lanterns, the robust GRP and solid core Composite Doors, the dependable Steel Security Doors, and an extensive range of additional services and products.

Herts Glass
& Security Solutions LTD

Office: 01923 624 660

Email: info@hertsglass.co.uk

Web: hertsglass.co.uk

  @hertsglass

Unit 1, Ashley House
Vale Industrial Estate,
Tolpits Lane
WD18 9QP



Expand your horizons with this slim,
thermally efficient sliding door.

EDGEGLIDE+
INLINE SLIDING DOOR



EDGEGLIDE+
INLINE SLIDING DOOR



Herts Glass
& Security Solutions LTD

- Modern Square Look
- Ultra Slim 35mm Interlock
- Up to 2.2m x 2.6m per panel
- Stylish Colour-Matched Hardware
- U-Value From 1.2 W/m²K
- Double or Triple Glazing
- Multi-Point Locking
- 70mm Frame Depth For Easy Replacement
- Kit Frame and Sash Option For Full Site-Assembly

EDGEGLIDE+

THE AMAZINGLY
SLEEK NEW INLINE
SLIDING DOOR

Choose your design, choose your view. EdgeGlide is the sleek sliding door which combines top quality, colour-matched hardware with elegant design. So the look of your door can match the look of your outdoors.

Size Limits

Maximum Panel Width	2200 mm
Maximum Panel Height	2600 mm
Maximum Panel Weight	240 kg

THRESHOLD HEIGHT	48 mm	
GLAZING THICKNESS	14 - 36 mm	
GLAZING METHOD	Wrap-Around	
GLAZING	Double or Triple	
SIGHTLINE (TYPICAL)	35 mm	
FRAME DEPTH	2 RAIL	70 mm
FRAME DEPTH	3 RAIL	126 mm

PERFORMANCE	
U-VALUE	From 1.2 W/m²K
AIR PERMEABILITY	Class 4
WATER TIGHTNESS	Class 7A
WIND RESISTANCE	Class C5
ENHANCED SECURITY	Multi-Point Locking
MAXIMUM ACOUSTIC INSULATION	40 dB Rw