



Herts Glass & Security Solutions Ltd proudly excels in producing cost-effective, creative, and innovative glazing and security solutions. Our exceptional team wholeheartedly embraces the essence of delivering impeccable customer care coupled with top-notch craftsmanship.

Our services cater to both the commercial and domestic sectors, extending our expertise to homeowners, architects, builders, and consultants, enabling them to manifest their visionary concepts throughout the picturesque landscapes of Hertfordshire and its neighbouring areas.

Embracing an extensive array of glazing and security solutions, we offer a plethora of options such as the exquisite Bi-Folds, the finest UPVC products, the regal Aluminium Front Doors, the indispensable Fire Exit Doors, the heavenly Skylights & Lanterns, the robust GRP and solid core Composite Doors, the dependable Steel Security Doors, and an extensive range of additional services and products.

Herts Glass & Security Solutions LTD

Office: 01923 624 660

Email: info@hertsglass.co.uk

Web: hertsglass.co.uk

[f](#) [@](#) [@hertsglass](#)

Unit 1 Ashley House
Vale Industrial Estate
Tolpits Lane
WD18 9QP



UNIFOLD^{HI}

BI-FOLD DOOR



Maximum Panel Width	1200 mm
Maximum Panel Height	3000 mm
Maximum Panel Weight	120 kg

Herts Glass & Security Solutions LTD

INSTALL EFFORTLESSLY
WITH THE UNIFOLD HI

Meet the Unifold HI, our new Bifold door with 110mm glass-to-glass sightlines, pre-gasketed snap-in glazing beads for effortless installation, options for PAS24 Certification and U values from as low as 0.8 W/m²K

SLIM 110MM GLASS TO GLASS SIGHTLINES

MODERN SQUARE LOOK

COLOUR-MATCHED HARDWARE

FULLY OPENABLE CORNERS

DOUBLE OR TRIPLE GLAZING

PAS24 CERTIFIED OPTIONS

MULTI-POINT LOCKING

BFRC RATING A++ TRIPLE GLAZED*

ADJUSTABLE JAMB OPTION

U VALUE FROM 0.8 W/M²K

FRAME DEPTH	80 mm
GLAZING THICKNESS	25-48 mm
GLAZING METHOD	Internally Beaded
GLAZING	Double or Triple
FINISHES	Single or Dual. All RAL Colours

PERFORMANCE	
U-VALUE	From 0.8 W/m ² K
AIR PERMEABILITY	Class 4
WATER TIGHTNESS	Class E750
WIND RESISTANCE	Class C3

ENHANCED SECURITY	
PAS24	Yes
MULTI-POINT LOCKING	Yes

THRESHOLD HEIGHT	
STANDARD	46.5 mm
LOW	28.5 mm

*on request